



Superior Technology & Best Quality at Cost Effective Price





Mini Bitumen Sprayer Super Model

FEATURES

- An attachment on Truck, tractor & Jeep.
- Chassis and linkage holder are entirely made of steel.
- Both Heating System, Wood Fire Bhatthi & Burner System
- 2.5 Ton Capacity.
- Heavy Duty Chassis & Structure.
- Safe & easy Operation.
- Hand Spray System.

TECHNICAL SPECIFICATION



Model	KDI 2500
Capacity	2500 Liters
Shape	U Shape
Insulation	40 mm thick with glass wool
Temp. Gauze	0 - 300°C
Main hole	450 mm in diameter
Mounting	Self chassis mounted on wheels
Pipe Length	3 meters
Type of Pipe	S.S. Corrugated hose pipe
Bitumen Spraying Pressure	0 - 3 kg. / cm2
1,5" x 1.5" Size positive displacement gear pump with output of 200-300 liters / min.	
Standard make Air Compressor	
Fuel consumption 7 - 8 liters / hour	
Capacity 5 liters	
Capacity 20 liters	
Standard make air cooled diesel engine	
	Capacity Shape Insulation Temp. Gauze Main hole Mounting Pipe Length Type of Pipe Bitumen Spraying Pressure 1,5" x 1.5" Size positive disp of 200-300 liters / min. Standard make Air Compres Fuel consumption 7 - 8 liters Capacity 5 liters Capacity 20 liters

Due to KDI Policy of continuous improvement / development, the technical data mentioned in this entire sheet is not binding and subject to change without notice.

KHODIYAR DEVELOPERS & INFRASTRUCTURE PVT. LTD.

Regd. Off. & Factory : 110, G.I.D.C.-II, Dediyasan, Mehsana, State - Gujarat, India. Ph. : +91-2762-224210, 224107, 098791 12730, Mob. 098250 82182

e-mail : kditechnology@gmail.com • website : www.kditechnology.com